



# Bona Pacific Filler<sup>®</sup>

Waterborne Wood Floor Filler

**High solids, waterborne compound designed for hardwood floors**



Bona Pacific Filler<sup>®</sup> is a high solid, waterborne compound specifically designed for filling cracks, holes, chips, gouges, and broken edges in hardwood floors prior to finishing. It is a ready-to-use formula, for spot or full-trowel filling. It has excellent adhesion, staining, and finishing properties with minimal shrinkage. For more accurate color matching, Bona Pacific Fillers can be blended together, tinted with universal tints, or mixed with fine edger dust to achieve the closest match possible.

- Thicker formula
- Sands easily
- Minimal clogging of sandpaper
- Accepts stain like wood
- GREENGUARD Indoor Air Quality Certified
- Available in 6 wood tones



# Bona Pacific Filler<sup>®</sup>

Waterborne Wood Floor Filler

**High solids, waterborne compound designed for hardwood floors**

## PHYSICAL CHARACTERISTICS

**Ingredients** – Inorganic fillers, water, binders, pigments

**Colors** – Red Oak, White Oak, Ash-Maple-Pine, Brazilian Cherry, American Cherry, Walnut

**Odor** – Mild latex odor

**Solids** – 65-75%

**Density** – 13.3 lbs./gallon (1.60 SG)

**US Regulatory VOC** – 100 g/L (0.8 lbs./gal)

**Stability** – Two year shelf life in unopened container

## APPLICATION CHARACTERISTICS

**Drying Time** – 30 minutes to 2 hours, depending on environmental conditions (temperature and humidity), coverage rate, and size of cracks and holes.

**Coverage** – 600-800 square feet per gallon

**Application Tools** – Putty knife, Bona<sup>®</sup> Trowel

## RECOMMENDED USE

Apply over bare wood before final sanding cut. Formulated for use with Bona DriFast<sup>®</sup> Stain, all Bona<sup>®</sup> waterborne and all other Bona finishing systems. Always prepare a test sample on a small area to determine compatibility and color acceptance

**BEFORE USING, READ ALL DIRECTIONS AND SAFETY DATA SHEETS.**

**FOR TECHNICAL ADVICE:** Call Bona US at 800-872-5515

## RESPONSE

In case of eye contact, flush immediately with water. Get medical attention if irritation occurs. For skin, wash thoroughly with soap and water. If affected by inhalation, remove to fresh air. If swallowed, drink 1 or 2 glasses of water to dilute. Do not induce vomiting. Get medical attention if symptoms occur.

## COMPATIBILITY

Bona Pacific Filler will accept most stains, sealers and finishes in the same manner as most woods. ALWAYS PREPARE A TEST OR SAMPLE AREA TO DETERMINE COMPATIBILITY. Do not use wood bleach over Bona Pacific Filler as it may damage the filler.

## SANDING AND FINISHING NEW FLOORS

Sand and prepare floor using accepted industry association methods.

## THE BONA Pacific Filler<sup>®</sup> SYSTEM

Bona Pacific Filler brand hardwood floor filler is a high solids content, waterborne compound specifically designed for filling cracks, holes, chips, gouges, and broken edges in hardwood floors prior to finishing. This product has excellent adhesion, staining and finishing properties with minimum shrinkage.

## RECOMMENDED APPLICATORS

Bona Steel Trowel, putty knife

## MIXING INSTRUCTIONS

Stir thoroughly before using. One to two cups of water may be added per gallon.

## FILLING

Apply Bona Pacific Filler 600-800 sq. ft. per gallon before final sanding with the drum or belt machine. Thoroughly vacuum dust from cracks and holes before filling. Work the filler as deep as possible into cavities. To fill and level larger holes or deeper cracks, several applications may be required. It may be necessary to trowel-fill the entire floor, depending upon the extent of cracks between strip or parquet floors. Allow sufficient drying time: 30 minutes to 2 hours before final sanding.



# Bona Pacific Filler<sup>®</sup>

Waterborne Wood Floor Filler

**High solids, waterborne compound designed for hardwood floors**

Higher humidity or cooler conditions will increase the drying time.

Bona Pacific Filler is tintable with universal color tints. Do not exceed more than 1 ounce of tint per gallon of filler. Use the Bona Pacific Filler that is closest in color to the floor being finished.

## CLEAN UP

Clean tools with water

## STORAGE AND DISPOSAL

Store at room temperature. Keep container closed when not in use. Do not store above 100° F (38° C).

## ORDERING INFORMATION

Item #	Color	Size	No./Case	Weight (lbs.)
AF0001822	Red Oak	Quart	8	32.35
AF0001823	White Oak	Quart	8	32.5
AF0001826	Ash/Maple/Pine	Quart	8	32.4
AF0001827	Brazilian Cherry	Quart	8	33.05
AF0001829	American Cherry	Quart	8	32
AF0001831	Walnut	Quart	8	32.85
AF0001539	Red Oak	Gallon	2	34.1
AF0001824	White Oak	Gallon	2	32.9
AF0001537	Ash/Maple/Pine	Gallon	2	33.15
AF0001828	Brazilian Cherry	Gallon	2	33.05
AF0001830	American Cherry	Gallon	2	33
AF0001832	Walnut	Gallon	2	33.1
AF0001821	Red Oak	3.5 Gallon	1	55.2
AF0001825	White Oak	3.5 Gallon	1	55.6
AF0001820	Ash/Maple/Pine	3.5 Gallon	1	56.1
AT959201	Bona Steel Trowel	N/A	1	N/A